

## **Technical Data Sheet**

Pressure / Temperature / Humidity / Air Velocity / Airflow / Sound level

## KIGAZ 150

가



- 가

- 680 g (

- 5

- IP40

: 331 x 112 x 86 mm

: 180 mm : 2.50 m

- 3.5" TFT-LCD grey display

, 5

(neoprene) (neoprene)

: ABS



O2, CO (H2



가



- H2 CO  $0 \sim 8,000 \text{ ppm}$ - 2 GB (100,000



	03/10/11 13:54:10
Accueil	
Mesures	
Configuration	•
Clients	•
Infos	•

		03/10/11 13:55:26			
Gaz naturel					
02	4.3 17.6	52.6			
CO ppm	0 y	1.26			
CO₂ %	9.3 %	98.8			
Ta °C	28.5 %	102.3			
	MANUAL PROPERTY.				

가 02 가 가 CO CO (H2 CO<sub>2</sub> 가 CO<sub>2</sub> max

가

5가 가

15가 가

PC - USB - Bluetooth®( (3.6V, 4,400 mA) - 10 - -5 ~ +50 <sup>1</sup>Combustibles: Sahara/Fos-sur-Mer Natural Gas, Groningen Natural Gas, Russia/North Sea Natural Gas, Propane, LPG, Butane, Light Oil, Heavy Oil, Bituminous coal, Hard coal, Coke gas, Bio fuel 5%, Wood 20%, Wood-chip 21%, Pellet 8% - -10 ~ +50

				*
0	Electro-chemical	from 0% to 21%	0.1% vol.	±0.2% vol.
CO (H2 )	Electro-chemical	from 0 to 8000 ppm	1 ppm	From 0 to 200 ppm : ±10 ppm From 201 to 2000 ppm : ±5% of the measured value From 2001 to 8000 ppm : ±10% of the measured value
가	K thermocouple	from -100 to +1250°C	0.1°C	±1.1°C or ±0.4% of measured value
	Internal NTC	From -20 to +120°C	0.1°C	±0.5°C
	Pt100 (1/3 Din external probe)	From -50 to +250°C	0.1°C	±0.3% of the measured value ±0.25°C
( )	Calculated**	From 0 to +99°Ctd	0.1°C	
	TcK (external probe)	From -200 to +1300 °C	0.1°C	±1.1°C or ±0.4% of measured value
	Semiconductor	From -200 to +200 hPa	0.01 hPa	From -200.00 to -1.00 hPa: $\pm 0.5\%$ of the measured value +0.045 Pa From -1.00 to -0.40 hPa: $\pm 5\%$ of the measured value From -0.40 to 0.40 hPa: $\pm 0.02$ hPa From 0.40 to 1.00 hPa: $\pm 5\%$ of the measured value From 1.00 to 200.00 hPa: $\pm 0.5\%$ of the measured value + 0.045 hPa
가	Calculated**	From 0 to 100%	0.1%	
(λ)	Calculated**	From 1 to 9.99	0.01	
( ηs)	Calculated**	From 0 to 100%	0.1 %	
(ηt) ( )	Calculated**	From 0 to 120%	0.1%	
(opacity index)		From 0 to 9		

\*All accuracies indicated in this document were stated in laboratory conditions and can be guaranteed for measurements carried out in the same conditions, or carried out with required compensation.
\*\*Calculation is made based on the measured values by the analyzer.

• KIGAZ100 가 / • 180mm 가 ( )

• LIGAZ

•

,

2 x 1m

•

.



KIGA150 : 2 - O2, CO (H2 )

• SCOT: CO • SCO2T: CO2

• **SPA 150SP** : Pt100

• SKCT:

• KEG : 가 • PMO :

Bluetooth®

• SCI:

• KDIP:



• **SDFG** : 가 (CH4)

